

# Joint Modelling of Behavioural and Brain Imaging Data

**Peter Tiño, Yuan Shen, Zoe Kourtzi, Rui Wang, Nahed Alowadi**

PT - School of Computer Science  
University of Birmingham  
UK

## **Foundational research in AI, Mach Learning, Natural Comp:**

- learning theory
- state space models and dynamical systems
- coevolutionary dynamics, population based approaches to optimisation

## **Methodology advancements:**

- metric learning
- [blending modelling with machine learning](#)

## **Inter- and cross-disciplinary research (extract science from data):**


- astronomy
- [cognitive neuroscience](#)
- biomedical sciences
- computational finance

# Behavioral experiment

- 4 abstract symbols (retaining no semantic meaning/relationships)
- participants exposed to symbolic series over this alphabet generated by 0-, 1st- or 2nd- order Markov models.
- Markov models (actually VLMM) constructed in a hierarchical manner (to study possible transfer of information)
- after seeing a block of symbols there is a gap - participants are asked to predict what comes next (chose one of the 4 symbols presented in the screen in randomized positions).

Kourtzi, Wang, Shen, Tino, Welchman. *The Journal of Neuroscience*, 37(35), pp. 84128427, 2017.

# Figure 1 Experimental setup




b

Level-0: Zero-order model


A	B	C	D
0.18	0.72	0.05	0.05

Level-1: First-order model



Level-1	Target			
	A	B	C	D
Context A		0.8	0.2	
Context B			0.8	0.2
Context C	0.2			0.8
Context D	0.8	0.2		

Level-2: Second-order model



Level-2	Target			
	A	B	C	D
Context A		0.8	0.2	
Context D	0.8	0.2		
Context AB	0.2	0.8		
Context XB			0.8	0.2
Context BC		0.2	0.8	
Context YC	0.2			0.8

# Questions to investigate

- would like to investigate
  - transfer of knowledge across levels
  - transfer of learning capabilities across levels
  - higher level groupings of participants
  - strategies for coping with increasingly complex stimuli (environment) - probability matching/maximization
- BUT - sparse data difficult to capture - each participant saw a different series of symbols, albeit generated from the same source
- difficult to approach in a standard ML framework
- describe each participant (data item) by an associated model that captures his/her learning behaviour

# Model that Tracks Participants' Learning

- Mixture of Markov models of order  $k = 0, 1, 2$
- Predictive distribution for the  $t$ -th gap item:

$$p(s_t | s_{t-2} s_{t-1}) = w_0 \cdot p_0(s_t | \emptyset) + w_1 \cdot p_1(s_t | s_{t-1}) + w_2 \cdot p_2(s_t | s_{t-2} s_{t-1})$$

- Probability vector  $\mathbf{w}$  is of central importance. Its time evolution  $\mathbf{w}_t$  shows how a participant learned the correct set of contexts
- Bayesian approach to update  $\mathbf{w}_t$ .

# Quantification Measures on the Models

- How well did a participant learn the underlying source?

$$\text{KL}(\mathcal{M}^{true,k} || \mathcal{M}_t^{tracking,k}) = \sum_{c \in \text{Context}^k} p^k(c) \cdot \text{KL}(p^k(\cdot|c) || p_t^k(\cdot|c))$$

- Probability maximization? To what degree?

$$\text{KL}(\mathcal{M}^{max,k} || \mathcal{M}_t^{tracking,k}) = \sum_{c \in \text{Context}^k} p^k(c) \cdot \text{KL}(p^{max,k}(\cdot|c) || p_t^k(\cdot|c))$$

where


$$p^{max,k}(s|c) = \begin{cases} \approx 1 & s = s^{\max} \\ \approx 0 & \text{otherwise} \end{cases} \quad \text{with} \quad s^{\max} = \underset{s}{\text{argmax}} p^k(s|c).$$

- Probability maximization or matching?

$$\mathcal{D}_t^{strategy} = \text{KL}(\mathcal{M}^{max,k} || \mathcal{M}_t^{tracking,k}) - \text{KL}(\mathcal{M}^{true,k} || \mathcal{M}_t^{tracking,k})$$

# Learning the Model Order

Figure 4




# Key Question

Does the participants grouping based on learning the **model order** carry on to other aspects of behavioural studies?


- transfer learning
- learning detailed source structure
- strategy choice (matching vs. maximization)

# Strategy Choice

Figure 6



## fMRI signals in ROIs - HPM modelling





# Simultaneous brain imaging and behavioral measurements

## group level fMRI modelling

fast vs. slow learners

Bayesian formulation: **shared** tight **parameter priors in each group**

**hierarchy of common/individualized within-group modelling**

Shen, Alowadi, Wang, Kourtzi, Tino. *Neural Comp*, under review.

# Regions of Interest

## ■ Frontal lobe

- **MFG** - middle frontal gyrus: attentional control.
- **SFG** - superior frontal gyrus: coordination with sensory system.

Both involved in learning, in particular, in sequential organization and self-monitoring of actions.





## ■ Limbic system

- **CG** - cingulate gyrus: integral part of the limbic system involved with emotion formation and processing, implicit learning and memory. Influential in linking motivational outcomes to behavior.





## ■ Basal ganglia

- **Pu** - putamen (lat. nutshell): Sub-cortical (dorsal stratum) associated with motor control, cognition, emotions and learning.

# HRF - time-to-peak



# Prototype volume



## ROI homogeneity

